



TEVO-CC600 360° all-in-one Conference Camera

360° all-in-one conference camera integrates a 360° camera, speaker, and voice-tracking microphones in a portable and stylish design. This all-in-one conference camera provides you a vivid face-to-face meeting experience by delivering high definition video with crystal clear audio. Combining a 360° camera, 4 omnidirectional microphones and full duplex speaker in an affordable package, it offers the features of auto framing and voice tracking that is unique at a budget price range. Plug-and-play and compatible with a variety of video conference platforms. It provides an easy-to-use, high-quality audio and video solution for remote conferencing in huddle-rooms.

Main Features:

- Portable and compact design;
- High definition CMOS sensor;
- 2.1MP with 4x lenses camera;
- Built-in 4x Omnidirectional microphones with 5 meters pickup range;
- One-tap display mode switching;
- Support 6 varied display modes;
- AI auto-tracking technology;
- Two-direction simultaneous voice tracking;
- USB Plug & Play;
- Compatible with most tripods;
- Supports your favorite video conferencing Apps.

Compatible Software:



More Details:

High definition CMOS Sensor



Crystal clear image with resolutions up to 1080p@30Hz. Built-in 4 x lenses, each camera with 2.1 Mega Pixels, deliver you vivid video images.

360° Panoramic Super Wide Angle View



360° Omnidirectional coverage with minimal distortion. Its 360° Omnidirectional & up-to 5 meters radius voice pickup capacity means you can host up to 10 participants.

USB Plug and Play



Plug & play, it's easy to start a meeting in a simple way. Portable design. Take video conferencing on the go. Carry Connection from meeting to meeting, or pack it when traveling so you will never miss the opportunity to meet face to face.

AI Tracking with Auto Framing



Adopt advanced Intelligent algorithm technology which recognizes and highlights the active speakers. (A green frame shows the active speaker) The camera automatically adjusts to keep participants centered within a few seconds.

Support 6 Varied Display Modes



Easy switch display modes for different presentation scenarios by touching the mode button.

1. Panorama Mode;
2. Top and Down Mode;
3. Composed Mode;
4. Speaker 1 Mode;
5. Speaker 2 Mode;
6. Pairing Mode.

Supports Your Favorite Video Conferencing Apps



Compatible with most Tripods. Compatible with mainstream software such as Skype, Microsoft Teams, Google Meet, Cisco, Zoom, BlueJeans, Amazon Chime, GoToMeeting, etc.

Technical Specification:

| | |
|--------------------------------|---|
| Product name | Meeting Go 360° conference camera |
| Image Sensor | 1/2.7" CMOS sensor |
| Lens Construction | 5 layer of glass+IRCF Elements |
| Effective Pixels | 2.1 Mega Pixels |
| Focal lens | F=2.49mm |
| Field of View | Horizontal: 360° / Vertical 60° FOV Top: Vertical + 45° up / - 15° down FOV Middle: Vertical ± 30° FOV-Down: Vertical + 20° up / -40° down |
| Resolution | Input: 4992x928 / 30fps, Output:1920x1080 / 30fps |
| Features | Adaptive ROI; People Tracking; Beamforming Tracking |
| Modes | Compose / Focus / Grid / Body fit / Speaker / Top-Down |
| Max Frame Rate | 2592H X 1944V@30fps 10 bits |
| Field of view | 140°(D), 140°(H), 103°(V) |
| Button | Mute Button (Touch SW);Mode Select Button, Switch H/W Image Output Mode and DOA |
| Microphone Array | Built-in 4 Digital Microphones |
| Pick up range | 5M |
| Far-Field Voice Capture | Support |
| Acoustic Echo Cancellation | Yes |
| Speaker | Full-Range Speaker x 1 |
| Response Frequency | 200 Hz to 8k Hz |
| Sound Pressure | 70db 1 (@1m at : pink noise 0dB) |
| Sound Playback Frequency Range | 200 Hz to 10k Hz |
| LED Display | Circularity 12*2 Blue LED Indicators / Touch Button Display RGB colors |
| Weight & Size | 447g(net weight), 67.5mm x 67.5mm x 182.3mm |

Package & Warranty:

What's in the box:

Video conference device, 12V 1A Power adaptor, USB-A-Type C cable(1 m), IR remote control, Quick start guide, Warranty card.

Dimension & Weight:

67.5 x 67.5 x 182.3mm /205.8 x 138 x 84.4mm (before / after packing)
0.5kg/1.5kg(Net weight / Gross weight)

