

# MARS H401B605S

## 5MP 4 IN 1 ColorVu Bullet Camera

---

Model: H401B605S

.....



.....

### Features:

- ❖ 5MP high quality image
- ❖ TVI/AHD/CVI/CVBS
- ❖ Supports white light illumination, 24/7 color images
- ❖ 3D noise reduction technology delivers clean and sharp images
- ❖ IP67 waterproof and dustproof design, high reliability
- ❖ Supports motion detection.

# MARS H401B605S

## Technical Specifications:

Model	H401B605S
<b>Sensor</b>	
Pixel	5MP
Size	1/3"
Minimum illumination	0.01 lux (F1.6, AGC ON) 0 lux (white light on)
<b>Lens</b>	
Lens	2.8mm
Lens mount	M12
Angle of view	H: 100.9° V: 56.5° D: 121.8°
<b>Illuminator</b>	
Illuminator	One white-light illuminator
Illumination distance	20m
Lifetime	≥60,000 hours
<b>Video</b>	
Resolution	5MP: 2592 (H) × 1944 (V) 4P: 2560 (H) × 1440 (V)
Frame rate	TVI/AHD/CVI: 5MP@12.5fps (default), 4MP@15fps CVBS: PAL, NTSC
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s - 1/50000s

# MARS H401B605S

Image	
Exposure mode	Four modes: Global (default), BLC, HLC, DWDR
Day/Night	24/7 color images
Digital noise reduction	2D/3D
White balance	Two modes: Auto (default), Manual
WDR	DWDR
Flip	NOT Supported
Defog	N/A
Interface	
Power	5.5mm power interface
Video output	BNC, supports TVI/AHD/CVI/CVBS
Operating environment	
Temperature	-30°C to 60°C (-22°F to 140°F)
Humidity	≤95% (RH, non-condensing)
Surge protection	4KV
General	
Power	DC 12V (±25%), with reverse polarity protection, Max 2.3W
Mount	Surface mount (default), optional backbox, pole mount bracket
Dimensions	142mm*63mm*65mm (L*W*H)
Material	Graphene + Plastic
Weight	500g(1.1lb)

# MARS H401B605S

Certification	
Certification	CE
Protection	IP67 (IEC 60529)